





TP 450 SLV FLOOR DIMENSION

TP 450 SLV





TECHNICAL SPECIFICATION

Machine Dimension	1931 x 1002 x 1435 (mm)
Power Supply	220V AC (50 Hz)
Power Consumption	1500 watts
Speed	450 Sheets/hour
Max Paper Size	482mm x 482mm 19" x 19" (Inch)
Min Paper Size	230mm x 280mm 9" x 11" (Inch)
Paper Thickness*	Min 0.13mm – Max 0.25mm
Гаре	Width 12mm Thickness 15mic.
Tape Material	Polyester
Air Compressor	Pneumatic Connection Required

FEATURES TP 450 SLV

Touch Panel Display

7"(Inch) Touch Control Display
Easy & User-friendly touch control program for V-Shape Layflat Binding

Auto Feeding

Auto Feeding: Electro Pneumatic feeder, is specially designed for inserting one sheet at a time. (Static charge should not be more than 3kw on paper surface for smooth single sheet feeding)

TWO Slitting Device (Window Cut)

One of the two Slitting device (cutter) is fixed and the other is adjustable in between the paper width.

Tape

Two Tape Rolls

- The transparent adhesive tape, is specially designed, to ensure proper holding of the joints and resulting in accurate binding.
- Auto Indication alerts, before the tape roll is about to finish.

Tape Finish

Gloss & Luster Finished tapes for the various types of media (Adhesive tapes holding strength may vary reference to media surface)

Auto Cut (Sheet Separator)

Built in automatic cutting system for cutting tapped sheets

V-Shape Process

Our patented V-Shape length cutting to arrange the paper in V-Shape for lay flat opening

Various Book Sizes Can Be Made | Single Or Multiple Ups Prints

G-2320/1-A, Almighty Gate, Metoda GIDC, Kalawad Road, Dist. Rajkot - 360021(Guj.) INDIA. Ph.: +91 2827 293266 Cell: +91 96876 99596

+91 98194 04036

E-mail:

sales@pinnacletechnocrats.com, info@pinnacletechnocrats.com, bhairav@pinnacletechnocrats.com